

## DG-16080

- 160 x 80 dots
- STN Reflective/EL/LED Backlight
- 1/80 Duty,

MECHANICAL DATA		
Item	Dimension	Unit
Module Size	100.0(W) x 54.0(H) x 11.0(T)	mm
View Area	72.3(W) x 37.8(H)	mm
Dot Size	0.39 x 0.39	mm
Dot Pitch	0.42x 0.42	mm

ABSOLUTELY MAXIMUM RATINGS					
Item	Symbol	Standard Value			Unit
		Min	Typ.	Max.	
Supply Voltage for Logic	$V_{DD} - V_{SS}$	0	--	7.0	V
Supply Voltage for LCD Drive	$V_{DD} - V_{EE}$	0	--	19.0	V
Input Voltage	$V_I$	$V_{SS}$	--	$V_{DD}$	V

PIN FUNCTIONS			
Pin No.	Symbol	Level	Function
1	$V_{SS}$		Ground
2	$V_{DD}$		Power Supply For Logic Circuit
3	$V_0$		Power Supply For LCD
4	RS	H/L	H→Instruction L→Data
5	R/W	H/L	H:Data Read, L:Data Write
6	E	H/L	Enable
7~14	DB0~DB7	H/L	Data Bus Line
15	CS	L	Chip Enable Active "L"

16	R <sub>ES</sub>	L	Reset Active "L"
17	R <sub>EE</sub>		Negative Voltage Output(-10V)
18~20	NC		

<b>ELECTRICAL CHARACTERISTICS</b>				
<b>Item</b>	<b>Symbol</b>	<b>Condition</b>	<b>Specification</b>	<b>Unit</b>
Logic circuit Power	V <sub>DD</sub>	--	4.75 →5.5	V
Supply Voltage	V <sub>0</sub>	--	-5.0 →20.0	V
EL Drive Voltage	V <sub>EL</sub>	f <sub>EL</sub> =500HZ	90 →110	V
Hight Level Output Voltage	V <sub>IH</sub>	V <sub>DD=5V</sub> ±0.25V	(0.7→ 1.0) x V <sub>DD</sub>	V
Low Level Output Voltage	V <sub>IL</sub>	V <sub>DD=5V</sub> ±0.25V	(0→ 0.3) x V <sub>DD</sub>	V
Hight Level Output Voltage	V <sub>OH</sub>	V <sub>DD=5V</sub> ±0.25V	2.4→ V <sub>DD</sub>	V
Low Level Output Voltage	I <sub>OL</sub>	V <sub>DD=5V</sub> ±0.25V	0→0.4	V
Current Consumption	I <sub>DD</sub>	V <sub>DD=5V</sub>	15.0MAX	mA
	I <sub>EE</sub>	V <sub>EE=-10V</sub>	4.0MAX	mA
	I <sub>EL</sub>	V <sub>EL=110V</sub> f <sub>EL</sub> =500HZ	20.0(AC)MAX	mA