

FEATURES

Conventional LED design : Simple to use

High Flux and Low Cost : More competitive advantages in the LED industry

Special body frame : Excellent transiting heat from LED chip operating under 150mA.

ADVANTAGES

Operating Current : 150mA .

Custom Design Light Sourcing Module for 0.4W

Excellent Heat Dissipation.

TYPICAL APPLICATIONS

Reading Light / Flashlight / Track Lighting

Under Shelf / Task Lighting

Emergency Lighting / Traffic Signals

Bollards / Security / Garden Lighting

Full Color Sign Boards



ABSOLUTE MAXIMUM RATINGS Tj=25°C

| Parameter | EP2034-150R1 | Units |
|--------------------------------------|--------------|-------|
| DC Forward Current | 150 | mA |
| Pulsed Forward Current | 500 | mA |
| Power Dissipation | 400 | mW |
| Dark Current (VR=5V) | 100 | uA |
| Operating Temperature Range | -20 to 80 | °C |
| Storage Temperature Range | -35 to 85 | °C |
| Soldering Temperature | 245 | °C |
| Thermal Resistance R θ (°C/W) | 85 | °C/W |
| LED Junction Temperature | 110 | °C |

Operating conditions:

1.Amber operating condition under f=0.5 ~ 2 Hz and 1/2 duty factor .

2. 520mw(White) : 6 pins of E-Power LED required soldering on PCB.

(PCB : 24.5 mm *24.5 mm , 1.6 t / two layers / 2.0 oz .)

3.Convective IR Reflow SolderingConvective IR Reflow Soldering.


ELECTRICAL CHARACTERISTICS

Tj=25°C IF=150mA

| Device Type | Forward Voltage VF (Volts) | | | Dark Current VR=5V IR=(uA) | | Intensity Iv (cd) | | Total Flux Φv (lm) | Wavelength λD (nm) | Viewing Angle 2θ 1/2 (Degrees) |
|--------------|-------------------------------|------|------|----------------------------------|------|-------------------------|------|--------------------------|--------------------------|--------------------------------------|
| | Min. | Typ. | Max. | Typ. | Max. | Min. | Typ. | Typ | Typ. | Typ. |
| EP2034-150R1 | 2.0 | 2.4 | 2.8 | 10 | 100 | 14 | 24 | 3 | 620 | 20° |

This specification is subject to change without notice.


OUTLINE DRAWINGS




NOTE

1. All dimensions are in millimeters.
2. Tolerance is 0.25mm unless otherwise specified.
3. This specification is subject to change without notice.


CHARACTERISTICS CURVE




Junction Temperature (°C)
RED




Forward Voltage VF (V)
RED




Forward Current (mA)
RED



TIME (min)
Soldering Temperature




VIEW ANGLE
EP2034-150XX




Wavelength (nm)
Spectral Distribution
RED

Operation Life




PIN CONNECTION

| COLOR | R | G | B | C | A |
|---------|--------|---|---|---|--------|
| ANODE | 6 | 6 | 6 | 6 | 6 |
| CATHODE | 2 5 | 3 | 3 | 3 | 2 5 |



TEST CIRCUIT

| COLOR | Vf (min) | R(100mA) | R(150mA) |
|-------|----------|----------|----------|
| R | 2.0V | 30 Ω | 20 Ω |



PART NO. SYSTEM OF E-Power LED

EP 2 03 4-150 R1

1---2-3-4-5-----6-----7

1.E -Power LED

2.YEAR 2002

3.PACKAGE TYPE:01=10mm LENS;03=5mm LENS;04=11 mm LENS

4.VIEWING ANGLE:4*5=20°

5.CURRENT:150mA

6.λD: R1=620nm (Red)