

**9.9mm(0.39")SINGLE DIGIT  
NUMERIC DISPLAY**




**SUN LED**

Email : sales@us.sunled.com

Web Site : www.sunled.com

XDMR08C-A




- Notes:**  
 1. All dimensions are in millimeters (inches), Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.  
 2. Specifications are subject to change without notice.

Absolute maximum ratings (T <sub>A</sub> =25°C)		MR (GaAlAs)	Unit
Reverse voltage	V <sub>R</sub>	5	V
Forward current	I <sub>F</sub>	30	mA
Forward current (peak) 1/10Duty cycle 0.1ms pulse width	i <sub>FS</sub>	155	mA
Power dissipation	P <sub>T</sub>	100	mW
Operating temperature	T <sub>A</sub>	-40 ~ +85	°C
Storage temperature	T <sub>stg</sub>		
Lead solder temperature [2mm below package base]	260°C For 5 Seconds		

Operating Characteristics (T <sub>A</sub> =25°C)		MR (GaAlAs)	Unit
Forward voltage (typ.) (I <sub>F</sub> =10mA)	V <sub>F</sub>	1.8	V
Forward voltage (max.) (I <sub>F</sub> =10mA)	V <sub>F</sub>	2.5	V
Reverse current (V <sub>R</sub> =5V)	I <sub>R</sub>	10	uA
Wavelength at peak emission (I <sub>F</sub> =10mA)	λ <sub>peak</sub>	660	nm
Wavelength at Dominate emission (I <sub>F</sub> =10mA)	λ <sub>D</sub>	640	nm
Spectral Line half-width (I <sub>F</sub> =10mA)	Δλ	20	nm
Capacitance (V <sub>F</sub> =0V, f=1MHz)	C	45	pF

Part Number	Emitting Color	Emitting Material	Luminous Intensity (I <sub>F</sub> =10mA) ucd		Wavelength nm λ <sub>P</sub>	Description
			min.	typ.		
XDMR08C-A	Red	GaAlAs	4700	15990	660	Common Cathode,Rt.Hand Decimal

**XDMR08C-A**



**◆MR**

