



Dual Common-Cathode Schottky Rectifier

TO-220AB



FEATURES

- Guardring for overvoltage protection
- Lower power losses, high efficiency
- Low forward voltage drop
- High forward surge capability
- High frequency operation
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

TYPICAL APPLICATIONS

For use in low voltage, high frequency rectifier of switching mode power supplies, freewheeling diodes, dc-to-dc converters or polarity protection applications.

PRIMARY CHARACTERISTICS

| | |
|-----------------------|----------|
| $I_{F(AV)}$ | 2 x 15 A |
| V_{RRM} | 40 V |
| E_{AS} | 20 mJ |
| I_{FSM} | 280 A |
| V_F at $I_F = 15$ A | 0.413 V |
| T_J max. | 150 °C |

MECHANICAL DATA

Case: TO-220AB

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test

Polarity: As marked

Mounting Torque: 10 in-lbs maximum

MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted)

| PARAMETER | SYMBOL | M30L40C | UNIT |
|--|----------------|---------------|------------|
| Maximum repetitive peak reverse voltage | V_{RRM} | 40 | V |
| Maximum average forward rectified current (Fig. 1) | $I_{F(AV)}$ | 30 15 | A |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load per diode | I_{FSM} | 280 | A |
| Peak repetitive reverse current per diode at $t_p = 2$ μ s, 1 kHz | I_{RRM} | 1.0 | A |
| Non-repetitive avalanche energy at 25 °C, $I_{AS} = 2$ A, $L = 10$ mH per diode | E_{AS} | 20 | mJ |
| Voltage rate of change (rated V_R) | dV/dt | 10 000 | V/ μ s |
| Operating junction and storage temperature range | T_J, T_{STG} | - 65 to + 150 | °C |



| ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | | | |
|---|--|---|--------|-------------------------|----------------|---------------------|
| PARAMETER | TEST CONDITIONS | | SYMBOL | TYP. | MAX. | UNIT |
| Instantaneous forward voltage per diode ⁽¹⁾ | $I_F = 8\text{ A}$ $I_F = 15\text{ A}$ $I_F = 30\text{ A}$ | $T_J = 25\text{ }^\circ\text{C}$ | V_F | 0.430 0.490 0.595 | - 0.55 - | V |
| | $I_F = 8\text{ A}$ $I_F = 15\text{ A}$ $I_F = 30\text{ A}$ | $T_J = 125\text{ }^\circ\text{C}$ | | 0.331 0.413 0.572 | - 0.48 - | |
| Reverse current per diode ⁽²⁾ | $V_R = 40\text{ V}$ | $T_J = 25\text{ }^\circ\text{C}$ $T_J = 100\text{ }^\circ\text{C}$ | I_R | 88 12 | 360 45 | μA mA |
| Typical junction capacitance per diode | 4.0 V, 1 MHz | | C_J | 750 | - | pF |

Notes:

- (1) Pulse test: 300 μs pulse width, 1 % duty cycle
- (2) Pulse test: Pulse width $\leq 40\text{ ms}$

| THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | |
|--|-----------------|---------|--------------------|
| PARAMETER | SYMBOL | M30L40C | UNIT |
| Typical thermal resistance per diode | $R_{\theta JC}$ | 2.0 | $^\circ\text{C/W}$ |

| ORDERING INFORMATION (Example) | | | | |
|--------------------------------|-----------------|------------------------|---------------|---------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| M30L40C-E3/4W | 2.068 | 4W | 50/tube | Tube |

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 2. Forward Power Loss Characteristics Per Diode




Figure 3. Typical Instantaneous Forward Characteristics Per Diode




Figure 5. Typical Junction Capacitance Per Diode




Figure 4. Typical Reverse Characteristics Per Diode





Figure 6. Typical Transient Thermal Impedance Per Diode

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

TO-220AB





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.