


High-Voltage Schottky Rectifier

High Barrier Technology for Improved High Temperature Performance



FEATURES

- Guardring for overvoltage protection
- Low power losses and high efficiency
- Low forward voltage drop
- Low leakage current
- High forward surge capability
- High frequency operation
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

TYPICAL APPLICATIONS

For use in middle voltage high frequency inverters, freewheeling, dc-to-dc converters, and polarity protection applications.

MECHANICAL DATA

Case: DO-201AD

Epoxy meets UL 94V-0 flammability rating

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix for consumer grade, meets JESD 201 class 1A whisker test, HE3 suffix for high reliability grade (AEC Q101 qualified), meets JESD 201 class 2 whisker test

Polarity: Color band denotes the cathode end

| PRIMARY CHARACTERISTICS | |
|-------------------------|-------------|
| $I_{F(AV)}$ | 3.0 A |
| V_{RRM} | 90 V, 100 V |
| I_{FSM} | 100 A |
| V_F | 0.65 V |
| I_R | 20 μ A |
| T_J max. | 175 °C |

| MAXIMUM RATINGS ($T_A = 25$ °C unless otherwise noted) | | | | |
|--|-------------|---------------|---------|------------|
| PARAMETER | SYMBOL | SB3H90 | SB3H100 | UNIT |
| Maximum repetitive peak reverse voltage | V_{RRM} | 90 | 100 | V |
| Maximum working reverse voltage | V_{RWM} | 90 | 100 | V |
| Maximum DC blocking voltage | V_{DC} | 90 | 100 | V |
| Maximum average forward rectified current at $T_L = 90$ °C | $I_{F(AV)}$ | 3.0 | | A |
| Peak forward surge current 8.3 ms single half sine-wave superimposed on rated load | I_{FSM} | 100 | | A |
| Peak repetitive reverse surge current at $t_p = 2.0$ μ s, 1 kHz | I_{RRM} | 1.0 | | A |
| Critical rate of rise of reverse voltage | dV/dt | 10 000 | | V/ μ s |
| Storage temperature range | T_{STG} | - 55 to + 175 | | °C |
| Maximum operating junction temperature | T_J | 175 | | °C |

| ELECTRICAL CHARACTERISTICS ($T_A = 25$ °C unless otherwise noted) | | | | | | |
|--|-----------------|----------------|--------|--------|---------|---------|
| PARAMETER | TEST CONDITIONS | | SYMBOL | SB3H90 | SB3H100 | UNIT |
| Maximum instantaneous forward voltage ⁽¹⁾ | $I_F = 3.0$ A | $T_J = 25$ °C | V_F | 0.80 | | V |
| | $I_F = 3.0$ A | $T_J = 125$ °C | | | | |
| Maximum reverse current at rated V_R ⁽²⁾ | | | I_R | 20 | | μ A |
| | | | | 4.0 | | mA |

Notes:

(1) Pulse test: 300 μ s pulse width, 1 % duty cycle

(2) Pulse test: Pulse width \leq 40 ms



| THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted) | | | | |
|--|-----------------|--------|---------|--------------------|
| PARAMETER | SYMBOL | SB3H90 | SB3H100 | UNIT |
| Maximum thermal resistance ⁽¹⁾ | $R_{\theta JA}$ | | 50 | $^\circ\text{C/W}$ |
| | $R_{\theta JL}$ | | 20 | |

Note:

(1) P.C.B. mounted with 0.2 x 0.2" (5.0 x 5.0 mm) copper pad areas

| ORDERING INFORMATION (Example) | | | | |
|--------------------------------|-----------------|------------------------|---------------|----------------------------------|
| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
| SB3H100-E3/54 | 1.09 | 54 | 1400 | 13" diameter paper tape and reel |
| SB3H100-E3/73 | 1.09 | 73 | 1000 | Ammo pack packaging |
| SB3H100HE3/54 ⁽¹⁾ | 1.09 | 54 | 1400 | 13" diameter paper tape and reel |
| SB3H100HE3/73 ⁽¹⁾ | 1.09 | 73 | 1000 | Ammo pack packaging |

Note:

(1) Automotive grade AEC Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Forward Current Derating Curve




Figure 3. Typical Instantaneous Forward Characteristics




Figure 2. Maximum Non-Repetitive Peak Forward Surge Current




Figure 4. Typical Reverse Characteristics




Figure 5. Typical Junction Capacitance





Figure 6. Typical Transient Thermal Impedance

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-201AD





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.