



20-V N-Channel 1.8-V (G-S) MOSFET

PRODUCT SUMMARY		
V _{DS} (V)	r _{DS(on)} (Ω)	I _D (A)
20	0.037 @ V _{GS} = 4.5 V	7.3
	0.039 @ V _{GS} = 2.5 V	7.1
	0.043 @ V _{GS} = 1.8 V	6.8


FEATURES

- TrenchFET® Power MOSFET
- New MICRO FOOT® Chipscale Packaging
Reduces Footprint Area Profile (0.62 mm) and On-Resistance Per Footprint Area

APPLICATIONS


- PA, Battery and Load Switch for Portable Devices

MICRO FOOT



Device Marking: 8402
xxx = Date/Lot Traceability Code

Ordering Information: Si8402DB-T1
Si8402DB-T1—E1 (Lead (Pb)-Free)



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T _A = 25°C UNLESS OTHERWISE NOTED)					
Parameter	Symbol	5 secs	Steady State	Unit	
Drain-Source Voltage	V _{DS}	20		V	
Gate-Source Voltage	V _{GS}	± 8			
Continuous Drain Current (T _J = 150°C) ^a	I _D	T _A = 25°C	7.3	5.3	A
		T _A = 70°C	5.9	4.3	
Pulsed Drain Current	I _{DM}	30		A	
continuous Source Current (Diode Conduction) ^a	I _S	2.3	1.2		
Maximum Power Dissipation ^a	P _D	T _A = 25°C	2.77	1.47	W
		T _A = 70°C	1.77	0.94	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	-55 to 150		°C	
Package Reflow Conditions ^b	VPR	215			
	IR/Convection	220			

THERMAL RESISTANCE RATINGS					
Parameter	Symbol	Typical	Maximum	Unit	
Maximum Junction-to-Ambient ^a	R _{thJA}	t ≤ 5 sec	35	45	°C/W
		Steady State	72	85	
Maximum Junction-to-Foot (drain)	R _{thJF}	16	20		

Notes

- Surface Mounted on 1" x 1" FR4 Board.
- Refer to IPC/JEDEC (J-STD-020A), no manual or hand soldering.



SPECIFICATIONS (T_J = 25 °C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = 250 μA	0.4		1.0	V
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 20 V, V _{GS} = 0 V			1	μA
		V _{DS} = 20 V, V _{GS} = 0 V, T _J = 70 °C			5	
On-State Drain Current ^a	I _{D(on)}	V _{DS} ≤ 5 V, V _{GS} = 4.5 V	5			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = 4.5 V, I _D = 1 A		0.031	0.037	Ω
		V _{GS} = 2.5 V, I _D = 1 A		0.033	0.039	
		V _{GS} = 1.8 V, I _D = 1 A		0.035	0.043	
Forward Transconductance ^a	g _{fs}	V _{DS} = 10 V, I _D = 1 A		12		S
Diode Forward Voltage ^a	V _{SD}	I _S = 1 A, V _{GS} = 0 V		0.8	1.2	V
Dynamic^b						
Total Gate Charge	Q _g	V _{DS} = 10 V, V _{GS} = 4.5 V, I _D = 1 A		17	26	nC
Gate-Source Charge	Q _{gs}			2		
Gate-Drain Charge	Q _{gd}			3.1		
Gate Resistance	R _g	f = 1 MHz		15		Ω
Turn-On Delay Time	t _{d(on)}	V _{DD} = 10 V, R _L = 10 Ω I _D ≅ 1 A, V _{GEN} = 4.5 V, R _g = 6 Ω		30	45	ns
Rise Time	t _r			45	70	
Turn-Off Delay Time	t _{d(off)}			145	220	
Fall Time	t _f			75	115	
Source-Drain Reverse Recovery Time	t _{rr}		I _F = 1 A, di/dt = 100 A/μs		30	







Notes

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
b. Guaranteed by design, not subject to production testing.





Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)




TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)



PACKAGE OUTLINE

MICRO FOOT: 4-BUMP (2 X 2, 0.8-mm PITCH)



NOTES (Unless Otherwise Specified):

5. Laser mark on the silicon die back, coated with a thin metal.
6. Bumps are Eutectic solder 63/37 Sn/Pb.
7. Non-solder mask defined copper landing pad.
8. The flat side of wafers is oriented at the bottom.

Dim	MILLIMETERS*		INCHES	
	Min	Max	Min	Max
A	0.600	0.650	0.0236	0.0256
A ₁	0.260	0.290	0.0102	0.0114
A ₂	0.340	0.360	0.0134	0.0142
b	0.370	0.410	0.0146	0.0161
D	1.520	1.600	0.0598	0.0630
E	1.520	1.600	0.0598	0.0630
e	0.750	0.850	0.0295	0.0335
S	0.370	0.380	0.0146	0.0150

* Use millimeters as the primary measurement.

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see <http://www.vishay.com/ppg?72657>.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.