

P-Channel 60-V (D-S) 175°C MOSFET

PRODUCT SUMMARY

V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A) ^c
-60	0.0093 @ $V_{GS} = -10$ V	-90
	0.0118 @ $V_{GS} = -4.5$ V	-90


FEATURES

- TrenchFET® Power MOSFET

APPLICATIONS


- DC/DC Primary Switch
- Automotive
 - 12-V Boardnet
 - High-Side Switches
 - Motor Drives

TO-220AB



Top View

DRAIN connected to TAB



P-Channel MOSFET

Ordering Information: SUP90P06-09L—E3

ABSOLUTE MAXIMUM RATINGS ($T_C = 25^\circ\text{C}$ UNLESS OTHERWISE NOTED)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	-60	V
Gate-Source Voltage	V_{GS}	± 20	
Continuous Drain Current ^c ($T_J = 175^\circ\text{C}$)	I_D	$T_C = 25^\circ\text{C}$	-90
		$T_C = 125^\circ\text{C}$	-67
Pulsed Drain Current	I_{DM}	-200	A
Avalanche Current	I_{AS}	-65	mJ
Single Pulse Avalanche Energy ^a	E_{AS}	211	
Power Dissipation	P_D	$T_C = 25^\circ\text{C}$	250 ^b
		$T_A = 25^\circ\text{C}$	2.4
Operating Junction and Storage Temperature Range	T_J, T_{stg}	-55 to 175	$^\circ\text{C}$

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Limit	Unit
Junction-to-Ambient Free Air	R_{thJA}	62	$^\circ\text{C}/\text{W}$
Junction-to-Case	R_{thJC}	0.6	

Notes:

- Duty cycle $\leq 1\%$.
- See SOA curve for voltage derating.
- Limited by package.







SPECIFICATIONS (T _J = 25 °C UNLESS OTHERWISE NOTED)						
Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	V _{(BR)DSS}	V _{GS} = 0 V, I _D = -250 μA	-60			V
Gate Threshold Voltage	V _{GS(th)}	V _{DS} = V _{GS} , I _D = -250 μA	-1		-3	
Gate-Body Leakage	I _{GSS}	V _{DS} = 0 V, V _{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = -60 V, V _{GS} = 0 V			-1	μA
		V _{DS} = -60 V, V _{GS} = 0 V, T _J = 125 °C			-50	
		V _{DS} = -60 V, V _{GS} = 0 V, T _J = 175 °C			-250	
On-State Drain Current ^a	I _{D(on)}	V _{DS} = -5 V, V _{GS} = -10 V	-120			A
Drain-Source On-State Resistance ^a	r _{DS(on)}	V _{GS} = -10 V, I _D = -30 A		0.0074	0.0093	Ω
		V _{GS} = -10 V, I _D = -30 A, T _J = 125 °C			0.0150	
		V _{GS} = -10 V, I _D = -30 A, T _J = 175 °C			0.0190	
		V _{GS} = -4.5 V, I _D = -20 A		0.0094	0.0118	
Forward Transconductance ^a	g _{fs}	V _{DS} = -15 V, I _D = -30 A	20			S
Dynamic^b						
Input Capacitance	C _{iss}	V _{GS} = 0 V, V _{DS} = -25 V, f = 1 MHz		9200		pF
Output Capacitance	C _{oss}			975		
Reversen Transfer Capacitance	C _{rss}			760		
Total Gate Charge ^c	Q _g	V _{DS} = -30 V, V _{GS} = -10 V, I _D = -90 A		160	240	nC
Gate-Source Charge ^c	Q _{gs}			40		
Gate-Drain Charge ^c	Q _{gd}			36		
Gate Resistance	R _g	f = 1.0 MHz		3		Ω
Turn-On Delay Time ^c	t _{d(on)}	V _{DD} = -30 V, R _L = 0.33 Ω I _D ≈ -90 A, V _{GEN} = -10 V, R _g = 2.5 Ω		20	30	ns
Rise Time ^c	t _r			190	285	
Turn-Off Delay Time ^c	t _{d(off)}			140	210	
Fall Time ^c	t _f			300	450	
Source-Drain Diode Ratings and Characteristics (T_C = 25 °C)^b						
Continuous Current	I _s				-90	A
Pulsed Current	I _{SM}				-200	
Forward Voltage ^a	V _{SD}	I _F = -50 A, V _{GS} = 0 V		-1.0	-1.5	V
Reverse Recovery Time	t _{rr}	I _F = -50 A, di/dt = 100 A/μs		60	90	ns
Peak Reverse Recovery Current	I _{RM(REC)}			-3	-4.5	A
Reverse Recovery Charge	Q _{rr}			0.09	0.2	μC

Notes:

- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
- b. Guaranteed by design, not subject to production testing.
- c. Independent of operating temperature.







TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)






TYPICAL CHARACTERISTICS (25 °C UNLESS NOTED)






THERMAL RATINGS


Maximum Avalanche and Drain Current vs. Case Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.