

# ACPL-214

## AC Input, Half-Pitch Phototransistor Optocoupler



## Data Sheet




### Description

The ACPL-214 is an AC-input single channel half-pitch phototransistor optocoupler which contains 2 light emitting diodes connected inversely parallel & optically coupled to a phototransistor. It is packaged in a 4-pin SO package.

The input-output isolation voltage is rated at 3000 Vrms. Response time,  $t_r$ , is  $2\mu s$  typically, while minimum CTR is 20% at input current of 5 mA

### ACPL-214 pin layout



- Pin 1 Anode
- Pin 2 Cathode
- Pin 3 Emitter
- Pin 4 Collector

### Features

- Current transfer ratio (CTR: 20% (min) at  $I_F = \pm 5mA$ ,  $V_{CC} = 5V$ )
- High input-output isolation voltage ( $V_{ISO} = 3,000V_{RMS}$ )
- Non-saturated Response time ( $t_r$ :  $2\mu s$  (typ) at  $V_{CC} = 10V$ ,  $I_C = 2mA$ ,  $R_L = 100\Omega$ )
- SO package
- CMR  $10kV/\mu s$  (typical)
- Safety and regulatory approvals
  - UL (pending)
  - CSA (pending)
  - IEC/EN/DIN EN 60747-5-2 (pending)
- Options available:
  - CTR Ranks 0, A

### Applications

- I/O Interface for Programmable controllers, computers.
- Sequence controllers
- System appliances, measuring instruments
- Signal transmission between circuits of different potentials and impedances.

## Ordering Information

ACPL-214-xxxx is pending UL Recognition with 3000 Vrms for 1 minute per UL1577 and is pending approval under CSA Component Acceptance Notice #5, File CA 88324.

Part number	RoHS Compliant Option		Package	Surface Mount	Tape & Reel	IEC/EN/DIN EN 60747-5-2	Quantity
	Rank '0' 20% <CTR< 400%	Rank 'A' 50% <CTR< 150%					
ACPL-214	-500E	-50AE	SO-4	x	x		3000 pcs per reel
	-560E	-56AE	SO-4	x	x	x	3000 pcs per reel

To order, choose a part number from the part number column and combine with the desired option from the option column to form an order entry.

Example 1:


ACPL-214-560E to order product of SO-4 Surface Mount package in Tape and Reel packaging with IEC/EN/DIN EN 60747-5-2 Safety Approval, 20%<CTR<400% and RoHS compliant.

Example 2:


ACPL-214-50AE to order product of SO-4 Surface Mount package in Tape and Reel packaging with 50%<CTR<150% and RoHS compliant.

Option datasheets are available. Contact your Avago sales representative or authorized distributor for information.

## Package Outline Drawings



## Solder Reflow Temperature Profile



- 1) One-time soldering reflow is recommended within the condition of temperature and time profile shown at right.
- 2) When using another soldering method such as infrared ray lamp, the temperature may rise partially in the mold of the device. Keep the temperature on the package of the device within the condition of (1) above.

Note: Non halide flux should be used.

## Absolute Maximum Ratings

Parameter	Symbol	ACPL-214	Units	Note
Storage Temperature	$T_S$	-55~125	°C	
Operating Temperature	$T_A$	-55~110	°C	
Average Forward Current	$I_{F(AVG)}$	±50	mA	
Pulse Forward Current	$I_{FSM}$	±1	A	
LED Power Dissipation	$P_I$	65	mW	
Collector Current	$I_C$	50	mA	
Collector-Emitter Voltage	$V_{CEO}$	80	V	
Emitter-Collector Voltage	$V_{ECO}$	7	V	
Isolation Voltage (AC for 1min, R.H. 40~60%)	$V_{ISO}$	3000	$V_{RMS}$	1min
Collector Power Dissipation	$P_C$	150	mW	
Total Power Dissipation	$P_{TOT}$	200	mW	
Lead Solder Temperature		260°C for 10 sec., 1.6 mm below seating plane		

## Electrical Specifications

Over recommended ambient temperature at 25°C unless otherwise specified.

Parameter	Symbol	Min.	Typ.	Max.	Units	Test Conditions	Note
Forward Voltage	$V_F$	-	1.2	1.4	V	$I_F = \pm 20\text{mA}$	Fig.6
Terminal Capacitance	$C_t$	-	60	-	pF	$V = 0, f = 1\text{MHz}$	
Collector Dark Current	$I_{CEO}$	-	-	100	nA	$V_{CE} = 48\text{V}, I_F = 0\text{mA}$	Fig.12
Collector-Emitter Breakdown Voltage	$BV_{CEO}$	80	-	-	V	$I_C = 0.5\text{mA}, I_F = 0\text{mA}$	
Emitter-Collector Breakdown Voltage	$BV_{ECO}$	7	-	-	V	$I_E = 100\ \mu\text{A}, I_F = 0\text{mA}$	
Current Transfer Ratio	CTR	20	-	400	%	$I_F = \pm 5\text{mA}, V_{CE} = 5\text{V}$	$\text{CTR} = (I_C/I_F) \times 100\%$
Saturated CTR	$\text{CTR}_{(\text{sat})}$	-	100	-	%	$I_F = \pm 1\text{mA}, V_{CE} = 0.4\text{V}$	
Collector-Emitter Saturation Voltage	$V_{CE(\text{sat})}$	-	-	0.4	V	$I_F = \pm 8\text{mA}, I_C = 2.4\text{mA}$	Fig.14
Isolation Resistance	Riso	$5 \times 10^{10}$	$1 \times 10^{11}$	-	$\Omega$	DC500V, R.H. 40~60%	
Floating Capacitance	$C_F$	-	0.8	1	pF	$V = 0, f = 1\text{MHz}$	
Cut-off Frequency (-3dB)	$F_C$	-	80	-	kHz	$V_{CC} = 5\text{V}, I_C = 2\text{mA}, R_L = 100\Omega$	Fig. 2,19
Response Time (Rise)	$t_r$	-	2	-	$\mu\text{s}$	$V_{CC} = 10\text{V}, I_C = 2\text{mA}, R_L = 100\Omega$	Fig. 1
Response Time (Fall)	$t_f$	-	3	-	$\mu\text{s}$		
Turn-on Time	$t_{\text{on}}$	-	3	-	$\mu\text{s}$		
Turn-off Time	$t_{\text{off}}$	-	3	-	$\mu\text{s}$		
Turn-ON Time	$t_{\text{ON}}$	-	2	-	$\mu\text{s}$	$V_{CC} = 5\text{V}, I_F = 16\text{mA}, R_L = 1.9\text{k}\Omega$	Fig. 1, 17
Storage Time	$T_S$	-	25	-	$\mu\text{s}$		
Turn-OFF Time	$t_{\text{OFF}}$	-	40	-	$\mu\text{s}$		
Common Mode Rejection Voltage	CMR	-	10	-	$\text{kV}/\mu\text{s}$	$T_a = 25^\circ\text{C}, R_L = 470\Omega, V_{CM} = 1.5\text{kV}(\text{peak}), I_F = 0\text{mA}, V_{CC} = 9\text{V}, V_{np} = 100\text{mV}$	Fig.20




Figure 1. Switching Time Test Circuit




Figure 2. Frequency Response Test Circuit




Figure 3. Forward Current vs. Ambient Temperature




Figure 4. Collector Power Dissipation vs. Ambient Temperature




Figure 5. Pulse Forward Current vs. Duty Cycle Ratio




Figure 6. Forward Current vs. Forward Voltage




Figure 7. Forward Voltage Temperature Coefficient vs. Forward Current




Figure 8. Pulse Forward Current vs. Pulse Forward Voltage




Figure 9. Collector Current vs. Collector-Emitter Voltage




Figure 10. Collector Current vs. Small Collector-Emitter Voltage




Figure 11. Collector Current vs. Forward Current




Figure 12. Collector Dark Current vs. Ambient Temperature




Figure 13. Current Transfer Ratio vs. Forward Current




Figure 14. Collector-Emitter Saturation Voltage vs. Ambient Temperature




Figure 15. Collector Current vs. Ambient Temperature




Figure 16. Switching Time vs. Load Resistance




Figure 17. Switching Time vs. Ambient Temperature




Figure 18. Collector-Emitter Saturation Voltage vs. Forward Current




Figure 19. Frequency Response




Figure 20. CMR Test Circuit

For product information and a complete list of distributors, please go to our web site: [www.avagotech.com](http://www.avagotech.com)

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies, Limited in the United States and other countries. Data subject to change. Copyright © 2007 Avago Technologies Limited. All rights reserved. AV02-0469EN - June 8, 2007