

SANYO	No.1060B	2SA1249/2SC3117
		PNP/NPN Epitaxial Planar Silicon Transistors 160V/1.5A Switching Applications

Uses

- Color TV sound output, converters, inverters

Features

- High breakdown voltage
- Large current capacity
- Adoption of MBIT process

() : 2SA1249

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector-to-Base Voltage	V _{CB0}	(-)180	V
Collector-to-Emitter Voltage	V _{CE0}	(-)160	V
Emitter-to-Base Voltage	V _{EBO}	(-)6	V
Collector Current	I _C	(-)1.5	A
Collector Current (Pulse)	I _{CP}	(-)2.5	A
Collector Dissipation	P _C	1	W
		10	W
Junction Temperature	T _j	150	°C
Storage Temperature	T _{stg}	-55 to +150	°C

T_c = 25°C


Electrical Characteristics at Ta = 25°C

			min	typ	max	unit
Collector Cutoff Current	I _{CBO}	V _{CB} = (-)120V, I _E = 0			(-)1.0	μA
Emitter Cutoff Current	I _{EBO}	V _{EB} = (-)4V, I _C = 0			(-)1.0	μA
DC Current Gain	h _{FE(1)}	V _{CE} = (-)5V, I _C = (-)100mA	100*		400*	
	h _{FE(2)}	V _{CE} = (-)5V, I _C = (-)10mA	90*			
Gain-Bandwidth Product	f _T	V _{CE} = (-)10V, I _C = (-)50mA		120		MHz
Output Capacitance	C _{ob}	V _{CB} = (-)10V, f = 1MHz		(22)		pF
C-E Saturation Voltage	V _{CE(sat)}	I _C = (-)500mA, I _B = (-)50mA	(-0.2)	(-0.5)		V
			0.13	0.45		
B-E Saturation Voltage	V _{BE(sat)}	I _C = (-)500mA, I _B = (-)50mA	(-)0.85	(-)1.2		V
C-B Breakdown Voltage	V _{(BR)CBO}	I _C = (-)10μA, I _E = 0	(-)180			V
C-E Breakdown Voltage	V _{(BR)CEO}	I _C = (-)1mA, R _{BE} = ∞	(-)160			V
E-B Breakdown Voltage	V _{(BR)EBO}	I _E = (-)10μA, I _C = 0	(-)6			V
Turn-ON Time	t _{on}	See specified Test Circuit.		0.04		μs
Storage Time	t _{stg}	See specified Test Circuit.	(0.7)	1.2		μs
Fall Time	t _f	See specified Test Circuit.	(0.04)	0.08		μs

*: The 2SA1249/2SC3117 are classified by 100mA h_{FE} as follows:


100 R 200	140 S 280	200 T 400
-----------	-----------	-----------

Switching Time Test Circuit



Package Dimensions 2009A









(unit: mm)





JEDEC: TO-126

B: Base
C: Collector
E: Emitter

2SA1249/2SC3117



2SA1249/2SC3117



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.