

DATA SHEET

NE/SA/SE5532/5532A

Internally-compensated dual low noise
operational amplifier

Product specification

1997 Sept 29

IC11 Data Handbook

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

DESCRIPTION

The 5532 is a dual high-performance low noise operational amplifier. Compared to most of the standard operational amplifiers, such as the 1458, it shows better noise performance, improved output drive capability and considerably higher small-signal and power bandwidths.

This makes the device especially suitable for application in high-quality and professional audio equipment, instrumentation and control circuits, and telephone channel amplifiers. The op amp is internally compensated for gains equal to one. If very low noise is of prime importance, it is recommended that the 5532A version be used because it has guaranteed noise voltage specifications.

FEATURES

- Small-signal bandwidth: 10MHz
- Output drive capability: 600Ω, 10V_{RMS}
- Input noise voltage: 5nV/√Hz (typical)
- DC voltage gain: 50000
- AC voltage gain: 2200 at 10kHz
- Power bandwidth: 140kHz
- Slew rate: 9V/μs
- Large supply voltage range: ±3 to ±20V
- Compensated for unity gain

PIN CONFIGURATIONS




Figure 1. Pin Configurations

ORDERING INFORMATION

| DESCRIPTION | TEMPERATURE RANGE | ORDER CODE | DWG # |
|--|-------------------|------------|----------|
| 8-Pin Plastic Dual In-Line Package (DIP) | 0 to 70°C | NE5532N | SOT97-1 |
| 8-Pin Plastic Dual In-Line Package (DIP) | -40°C to +85°C | SA5532N | SOT97-1 |
| 8-Pin Plastic Dual In-Line Package (DIP) | -40°C to +85°C | SA5532AN | SOT97-1 |
| 8-Pin Ceramic Dual In-Line Package (CERDIP) | 0 to 70°C | NE5532FE | 0580A |
| 8-Pin Plastic Dual In-Line Package (DIP) | 0 to 70°C | NE5532AN | SOT97-1 |
| 8-Pin Ceramic Dual In-Line Package (CERDIP) | 0 to 70°C | NE5532AF | 0580A |
| 8-Pin Ceramic Dual In-Line Package (CERDIP) | -55°C to +125°C | SE5532FE | 0580A |
| 8-Pin Ceramic Dual In-Line Package (CERDIP) | -55°C to +125°C | SE5532AF | 0580A |
| 8-Pin Small Outline Package (SO) | 0 to 70°C | NE5532AD8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -40°C to 85°C | SA5532D8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -40°C to 85°C | SA5532AD8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -55°C to +125°C | SE5532AD8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | 0 to 70°C | NE5532D8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -40°C to 85°C | SA5532D8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -40°C to 85°C | SA5532AD8 | SOT96-1 |
| 8-Pin Small Outline Package (SO) | -55°C to +125°C | SE5532D8 | SOT96-1 |
| 16-Pin Plastic Small Outline Large (SOL) Package | 0 to 70°C | NE5532D | SOT162-1 |
| 16-Pin Plastic Dual In-Line Package (DIP) | -55°C to +125°C | SE5532N | SOT38-4 |

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

EQUIVALENT SCHEMATIC (EACH AMPLIFIER)




Figure 2. Equivalent Schematic (Each Amplifier)

ABSOLUTE MAXIMUM RATINGS

| SYMBOL | PARAMETER | RATING | UNIT |
|-------------------|--|--------------------------------------|----------------------|
| V _S | Supply voltage | ±22 | V |
| V _{IN} | Input voltage | ±V _{SUPPLY} | V |
| V _{DIFF} | Differential input voltage ¹ | ±0.5 | V |
| T _A | Operating temperature range SA5532/A NE5532/A SE5532/A | -40 to +85 0 to 70 -55 to +125 | °C °C °C |
| T _{STG} | Storage temperature | -65 to +150 | °C |
| T _J | Junction temperature | 150 | °C |
| P _D | Maximum power dissipation, T _A =25°C (still-air) ² 8 D8 package 8 N package 8 FE package 16 D package | 780 1200 1000 1200 | mW mW mW mW |
| T _{SOLD} | Lead soldering temperature (10sec max) | 300 | °C |

NOTES:

- Diodes protect the inputs against over-voltage. Therefore, unless current-limiting resistors are used, large currents will flow if the differential input voltage exceeds 0.6V. Maximum current should be limited to ±10mA.
- Thermal resistances of the above packages are as follows:
 N package at 100°C/W
 F package at 135°C/W
 D package at 105°C/W
 D8 package at 160°C/W

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

DC ELECTRICAL CHARACTERISTICS

 $T_A=25^{\circ}\text{C}$ $V_S=\pm 15\text{V}$, unless otherwise specified. 1, 2, 3

| SYMBOL | PARAMETER | TEST CONDITIONS | SE/5532/5532A | | | NE/SA/5532/5532A | | | UNIT |
|--------------------------|------------------------------|---|---------------|------------|------|------------------|------------|------|------------------------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V_{OS} | Offset voltage | Over temperature | | 0.5 | 2 | | 0.5 | 4 | mV |
| $\Delta V_{OS}/\Delta T$ | | | | 5 | 3 | | 5 | 5 | mV/ $^{\circ}\text{C}$ |
| I_{OS} | Offset current | Over temperature | | | 100 | | 10 | 150 | nA |
| $\Delta I_{OS}/\Delta T$ | | | | 200 | 200 | | 200 | 200 | nA/ $^{\circ}\text{C}$ |
| I_B | Input current | Over temperature | | 200 | 400 | | 200 | 800 | nA |
| $\Delta I_B/\Delta T$ | | | | 5 | 700 | | 5 | 1000 | nA/ $^{\circ}\text{C}$ |
| I_{CC} | Supply current | Over temperature | | 8 | 10.5 | | 8 | 16 | mA |
| | | | | | | 13 | | | mA |
| V_{CM} | Common-mode input range | | ± 12 | ± 13 | | ± 12 | ± 13 | | V |
| CMRR | Common-mode rejection ratio | | 80 | 100 | | 70 | 100 | | dB |
| PSRR | Power supply rejection ratio | | | 10 | 50 | | 10 | 100 | $\mu\text{V/V}$ |
| A_{VOL} | Large-signal voltage gain | $R_L \geq 2\text{k}\Omega$, $V_O = \pm 10\text{V}$ | 50 | 100 | | 25 | 100 | | V/mV |
| | | Over temperature | 25 | | | 15 | | | V/mV |
| | | $R_L \geq 600\Omega$, $V_O = \pm 10\text{V}$ | 40 | 50 | | 15 | 50 | | V/mV |
| | | Over temperature | 20 | | | 10 | | | V/mV |
| V_{OUT} | Output swing | $R_L \geq 600\Omega$ | ± 12 | ± 13 | | ± 12 | ± 13 | | V |
| | | Over temperature | ± 10 | ± 12 | | ± 10 | ± 12 | | |
| | | $R_L \geq 600\Omega$, $V_S = \pm 18\text{V}$ | ± 15 | ± 16 | | ± 15 | ± 16 | | |
| | | Over temperature | ± 12 | ± 14 | | ± 12 | ± 14 | | |
| | | $R_L \geq 2\text{k}\Omega$ | ± 13 | ± 13.5 | | ± 13 | ± 13.5 | | |
| | | Over temperature | ± 12 | ± 12.5 | | ± 10 | ± 12.5 | | |
| R_{IN} | Input resistance | | 30 | 300 | | 30 | 300 | | k Ω |
| I_{SC} | Output short circuit current | | 10 | 38 | 60 | 10 | 38 | 60 | mA |

NOTES:

- Diodes protect the inputs against overvoltage. Therefore, unless current-limiting resistors are used, large currents will flow if the differential input voltage exceeds 0.6V. Maximum current should be limited to $\pm 10\text{mA}$.
- For operation at elevated temperature, derate packages based on the package thermal resistance.
- Output may be shorted to ground at $V_S = \pm 15\text{V}$, $T_A = 25^{\circ}\text{C}$. Temperature and/or supply voltages must be limited to ensure dissipation rating is not exceeded.

AC ELECTRICAL CHARACTERISTICS

 $T_A=25^{\circ}\text{C}$ $V_S=\pm 15\text{V}$, unless otherwise specified.

| SYMBOL | PARAMETER | TEST CONDITIONS | NE/SA/SE5532/5532A | | | UNIT |
|-----------|------------------------|---|--------------------|-----|-----|------------------|
| | | | Min | Typ | Max | |
| R_{OUT} | Output resistance | $A_V=30\text{dB}$ Closed-loop $f=10\text{kHz}$, $R_L=600\Omega$ | | 0.3 | | Ω |
| | Overshoot | Voltage-follower $V_{IN}=100\text{mV}_{P-P}$ $C_L=100\text{pF}$, $R_L=600\Omega$ | | 10 | | % |
| A_V | Gain | $f=10\text{kHz}$ | | 2.2 | | V/mV |
| GBW | Gain bandwidth product | $C_L=100\text{pF}$, $R_L=600\Omega$ | | 10 | | MHz |
| SR | Slew rate | | | 9 | | V/ μs |
| | Power bandwidth | $V_{OUT}=\pm 10\text{V}$ | | 140 | | kHz |
| | | $V_{OUT}=\pm 14\text{V}$, $R_L=600\Omega$, $V_{CC}=\pm 18\text{V}$ | | 100 | | kHz |

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

ELECTRICAL CHARACTERISTICS

$T_A=25^\circ\text{C}$ $V_S=\pm 15\text{V}$, unless otherwise specified.

| SYMBOL | PARAMETER | TEST CONDITIONS | NE/SE5532 | | | NE/SA/SE5532A | | | UNIT |
|--------------------|---------------------|---|-----------|-----|-----|---------------|-----|-----|------------------------------|
| | | | Min | Typ | Max | Min | Typ | Max | |
| V_{NOISE} | Input noise voltage | $f_O=30\text{Hz}$ $f_O=1\text{kHz}$ | | 8 | | | 8 | 12 | $\text{nV}/\sqrt{\text{Hz}}$ |
| | | | | 5 | | | 5 | 6 | $\text{nV}/\sqrt{\text{Hz}}$ |
| I_{NOISE} | Input noise current | $f_O=30\text{Hz}$ $f_O=1\text{kHz}$ | | 2.7 | | | 2.7 | | $\text{pA}/\sqrt{\text{Hz}}$ |
| | | | | 0.7 | | | 0.7 | | $\text{pA}/\sqrt{\text{Hz}}$ |
| | Channel separation | $f=1\text{kHz}$, $R_S=5\text{k}\Omega$ | | 110 | | | 110 | | dB |

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 3. Typical Performance Characteristics

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

TEST CIRCUITS






Figure 4. Test Circuits

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

DIP8: plastic dual in-line package; 8 leads (300 mil)

SOT97-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT | A max. | A ₁ min. | A ₂ max. | b | b ₁ | b ₂ | c | D ⁽¹⁾ | E ⁽¹⁾ | e | e ₁ | L | M _E | M _H | w | Z ⁽¹⁾ max. |
|--------|--------|---------------------|---------------------|----------------|----------------|----------------|----------------|------------------|------------------|------|----------------|--------------|----------------|----------------|-------|-----------------------|
| mm | 4.2 | 0.51 | 3.2 | 1.73 1.14 | 0.53 0.38 | 1.07 0.89 | 0.36 0.23 | 9.8 9.2 | 6.48 6.20 | 2.54 | 7.62 | 3.60 3.05 | 8.25 7.80 | 10.0 8.3 | 0.254 | 1.15 |
| inches | 0.17 | 0.020 | 0.13 | 0.068 0.045 | 0.021 0.015 | 0.042 0.035 | 0.014 0.009 | 0.39 0.36 | 0.26 0.24 | 0.10 | 0.30 | 0.14 0.12 | 0.32 0.31 | 0.39 0.33 | 0.01 | 0.045 |

Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|----------|------|---------------------|----------------------|
| | IEC | JEDEC | EIAJ | | |
| SOT97-1 | 050G01 | MO-001AN | | | 92-11-17 95-02-04 |




Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

0580A 8-PIN (300 mils wide) CERAMIC DUAL IN-LINE (F) PACKAGE

NOTES:

1. Controlling dimension: Inches. Millimeters are shown in parentheses.
2. Dimension and tolerancing per ANSI Y14. 5M-1982.
3. "T", "D", and "E" are reference datums on the body and include allowance for glass overrun and meniscus on the seal line, and lid to base mismatch.
4. These dimensions measured with the leads constrained to be perpendicular to plane T.
5. Pin numbers start with Pin #1, and continue counterclockwise to Pin #8 when viewed from the top.




Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

SO8: plastic small outline package; 8 leads; body width 3.9mm

SOT96-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT | A max. | A ₁ | A ₂ | A ₃ | b _p | c | D ⁽¹⁾ | E ⁽²⁾ | e | H _E | L | L _p | Q | v | w | y | Z ⁽¹⁾ | θ |
|--------|--------|------------------|----------------|----------------|----------------|------------------|------------------|------------------|-------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm | 1.75 | 0.25 0.10 | 1.45 1.25 | 0.25 | 0.49 0.36 | 0.25 0.19 | 5.0 4.8 | 4.0 3.8 | 1.27 | 6.2 5.8 | 1.05 | 1.0 0.4 | 0.7 0.6 | 0.25 | 0.25 | 0.1 | 0.7 0.3 | 8° 0° |
| inches | 0.069 | 0.0098 0.0039 | 0.057 0.049 | 0.01 | 0.019 0.014 | 0.0098 0.0075 | 0.20 0.19 | 0.16 0.15 | 0.050 | 0.24 0.23 | 0.041 | 0.039 0.016 | 0.028 0.024 | 0.01 | 0.01 | 0.004 | 0.028 0.012 | |

Notes

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.
2. Plastic or metal protrusions of 0.25 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|----------|------|--|---------------------|----------------------|
| | IEC | JEDEC | EIAJ | | | |
| SOT96-1 | 076E03S | MS-012AA | | | | 92-11-17 95-02-04 |

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

SO16: plastic small outline package; 16 leads; body width 7.5 mm

SOT162-1



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT | A max. | A ₁ | A ₂ | A ₃ | b _p | c | D ⁽¹⁾ | E ⁽¹⁾ | e | H _E | L | L _p | Q | v | w | y | Z ⁽¹⁾ | θ |
|--------|--------|----------------|----------------|----------------|----------------|----------------|------------------|------------------|-------|----------------|-------|----------------|----------------|------|------|-------|------------------|----------|
| mm | 2.65 | 0.30 0.10 | 2.45 2.25 | 0.25 | 0.49 0.36 | 0.32 0.23 | 10.5 10.1 | 7.6 7.4 | 1.27 | 10.65 10.00 | 1.4 | 1.1 0.4 | 1.1 1.0 | 0.25 | 0.25 | 0.1 | 0.9 0.4 | 8° 0° |
| inches | 0.10 | 0.012 0.004 | 0.096 0.089 | 0.01 | 0.019 0.014 | 0.013 0.009 | 0.41 0.40 | 0.30 0.29 | 0.050 | 0.42 0.39 | 0.055 | 0.043 0.016 | 0.043 0.039 | 0.01 | 0.01 | 0.004 | 0.035 0.016 | |

Note

1. Plastic or metal protrusions of 0.15 mm maximum per side are not included.


| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|----------|------|--|---------------------|-----------------------|
| | IEC | JEDEC | EIAJ | | | |
| SOT162-1 | 075E03 | MS-013AA | | | | -92-11-17 95-01-24 |

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

DIP16: plastic dual in-line package; 16 leads (300 mil)

SOT38-4



DIMENSIONS (inch dimensions are derived from the original mm dimensions)

| UNIT | A max. | A ₁ min. | A ₂ max. | b | b ₁ | b ₂ | c | D ⁽¹⁾ | E ⁽¹⁾ | e | e ₁ | L | M _E | M _H | w | Z ⁽¹⁾ max. |
|--------|--------|---------------------|---------------------|----------------|----------------|----------------|----------------|------------------|------------------|------|----------------|--------------|----------------|----------------|-------|-----------------------|
| mm | 4.2 | 0.51 | 3.2 | 1.73 1.30 | 0.53 0.38 | 1.25 0.85 | 0.36 0.23 | 19.50 18.55 | 6.48 6.20 | 2.54 | 7.62 | 3.60 3.05 | 8.25 7.80 | 10.0 8.3 | 0.254 | 0.76 |
| inches | 0.17 | 0.020 | 0.13 | 0.068 0.051 | 0.021 0.015 | 0.049 0.033 | 0.014 0.009 | 0.77 0.73 | 0.26 0.24 | 0.10 | 0.30 | 0.14 0.12 | 0.32 0.31 | 0.39 0.33 | 0.01 | 0.030 |

Note

1. Plastic or metal protrusions of 0.25 mm maximum per side are not included.

| OUTLINE VERSION | REFERENCES | | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|-------|------|--|---------------------|-----------------------|
| | IEC | JEDEC | EIAJ | | | |
| SOT38-4 | | | | | | -92-11-17 95-01-14 |

Internally-compensated dual low noise operational amplifier

NE/SA/SE5532/5532A

DEFINITIONS

| Data Sheet Identification | Product Status | Definition |
|----------------------------------|-------------------------------|--|
| <i>Objective Specification</i> | Formative or in Design | This data sheet contains the design target or goal specifications for product development. Specifications may change in any manner without notice. |
| <i>Preliminary Specification</i> | Preproduction Product | This data sheet contains preliminary data, and supplementary data will be published at a later date. Philips Semiconductors reserves the right to make changes at any time without notice in order to improve design and supply the best possible product. |
| <i>Product Specification</i> | Full Production | This data sheet contains Final Specifications. Philips Semiconductors reserves the right to make changes at any time without notice, in order to improve design and supply the best possible product. |

Philips Semiconductors and Philips Electronics North America Corporation reserve the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no license or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified. Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

LIFE SUPPORT APPLICATIONS

Philips Semiconductors and Philips Electronics North America Corporation Products are not designed for use in life support appliances, devices, or systems where malfunction of a Philips Semiconductors and Philips Electronics North America Corporation Product can reasonably be expected to result in a personal injury. Philips Semiconductors and Philips Electronics North America Corporation customers using or selling Philips Semiconductors and Philips Electronics North America Corporation Products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors and Philips Electronics North America Corporation for any damages resulting from such improper use or sale.

Philips Semiconductors
811 East Arques Avenue
P.O. Box 3409
Sunnyvale, California 94088-3409
Telephone 800-234-7381

© Copyright Philips Electronics North America Corporation 1997
 All rights reserved. Printed in U.S.A.

print code

Date of release: 04-96

Document order number:

9397 750 01699

Let's make things better.