

**Small Signal Product**

**5% Tolerance SMD Zener Diode**

**FEATURES**

- Wide zener voltage range selection: 2.4V to 75V
- VZ Tolerance Selection of ±5%
- Hermetically sealed glasses
- Moisture sensitivity level 1
- Matte Tin(Sn) lead finish with Nickel(Ni) underplate
- Pb free and RoHS compliant
- High reliability glass passivation insuring parameter stability and protection against junction contamination



**Mini-MELF (LL34)**

Hermetically Sealed Glass


**MECHANICAL DATA**

- Case: Mini-MELF Package (JEDEC DO-213AC)
- High temperature soldering guaranteed: 270°C/10s
- Polarity: Indicated by cathode band
- Weight: 31 mg (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted) |                                   |              |      |
|--|-----------------------------------|--------------|------|
| PARAMETER  | SYMBOL                            | VALUE        | UNIT |
| Power Dissipation  | P <sub>D</sub>                    | 500          | mW   |
| Forward Voltage  | I <sub>F</sub> = 10 mA            | 1            | V    |
| Thermal Resistance (Junction to Ambient)   | (Note 1) R <sub>θJA</sub>         | 300          | °C/W |
| Junction and Storage Temperature Range   | T <sub>J</sub> , T <sub>STG</sub> | - 65 to +175 | °C   |

Note1: Valid provided that electrodes are kept at ambient temperature

**Zener I vs. V Characteristics**



- V<sub>BR</sub> : Voltage at I<sub>ZK</sub>
- I<sub>ZK</sub> : Test current for voltage V<sub>BR</sub>
- Z<sub>ZK</sub> : Dynamic impedance at I<sub>ZK</sub>
- I<sub>ZT</sub> : Test current for voltage V<sub>Z</sub>
- V<sub>Z</sub> : Voltage at current I<sub>ZT</sub>
- Z<sub>ZT</sub> : Dynamic impedance at I<sub>ZT</sub>
- I<sub>ZM</sub> : Maximum steady state current
- V<sub>ZM</sub> : Voltage at I<sub>ZM</sub>

Small Signal

ELECTRICAL CHARACTERISTICS (  $T_A = 25^\circ\text{C}$  unless otherwise noted )

| Part Number | $V_Z @ I_{ZT}$ (Volt) |     |      | $I_{ZT}$ (mA) | $Z_{ZT} @ I_{ZT}$ ( $\Omega$ )<br>Max | $I_{ZK}$ (mA) | $Z_{ZK} @ I_{ZK}$ ( $\Omega$ )<br>Max | $I_R @ V_R$ ( $\mu\text{A}$ )<br>Max | $V_R$ (V) |
|-------------|-----------------------|-----|------|---------------|---------------------------------------|---------------|---------------------------------------|--------------------------------------|-----------|
|             | Min                   | Nom | Max  |               |                                       |               |                                       |                                      |           |
| BZV55C2V4   | 2.28                  | 2.4 | 2.56 | 5             | 85                                    | 1.0           | 600                                   | 50                                   | 1.0       |
| BZV55C2V7   | 2.51                  | 2.7 | 2.89 | 5             | 85                                    | 1.0           | 600                                   | 10                                   | 1.0       |
| BZV55C3V0   | 2.8                   | 3.0 | 3.2  | 5             | 85                                    | 1.0           | 600                                   | 4                                    | 1.0       |
| BZV55C3V3   | 3.1                   | 3.3 | 3.5  | 5             | 85                                    | 1.0           | 600                                   | 2                                    | 1.0       |
| BZV55C3V6   | 3.4                   | 3.6 | 3.8  | 5             | 85                                    | 1.0           | 600                                   | 2                                    | 1.0       |
| BZV55C3V9   | 3.7                   | 3.9 | 4.1  | 5             | 85                                    | 1.0           | 600                                   | 2                                    | 1.0       |
| BZV55C4V3   | 4.0                   | 4.3 | 4.6  | 5             | 75                                    | 1.0           | 600                                   | 1                                    | 1.0       |
| BZV55C4V7   | 4.4                   | 4.7 | 5.0  | 5             | 60                                    | 1.0           | 600                                   | 0.5                                  | 1.0       |
| BZV55C5V1   | 4.8                   | 5.1 | 5.4  | 5             | 35                                    | 1.0           | 550                                   | 0.1                                  | 1.0       |
| BZV55C5V6   | 5.2                   | 5.6 | 6.0  | 5             | 25                                    | 1.0           | 450                                   | 0.1                                  | 1.0       |
| BZV55C6V2   | 5.8                   | 6.2 | 6.6  | 5             | 10                                    | 1.0           | 200                                   | 0.1                                  | 2.0       |
| BZV55C6V8   | 6.4                   | 6.8 | 7.2  | 5             | 8                                     | 1.0           | 150                                   | 0.1                                  | 3.0       |
| BZV55C7V5   | 7.0                   | 7.5 | 7.9  | 5             | 7                                     | 1.0           | 50                                    | 0.1                                  | 5.0       |
| BZV55C8V2   | 7.7                   | 8.2 | 8.7  | 5             | 7                                     | 1.0           | 50                                    | 0.1                                  | 6.2       |
| BZV55C9V1   | 8.5                   | 9.1 | 9.6  | 5             | 10                                    | 1.0           | 50                                    | 0.1                                  | 6.8       |
| BZV55C10    | 9.4                   | 10  | 10.6 | 5             | 15                                    | 1.0           | 70                                    | 0.1                                  | 7.5       |
| BZV55C11    | 10.4                  | 11  | 11.6 | 5             | 20                                    | 1.0           | 70                                    | 0.1                                  | 8.2       |
| BZV55C12    | 11.4                  | 12  | 12.7 | 5             | 20                                    | 1.0           | 90                                    | 0.1                                  | 9.1       |
| BZV55C13    | 12.4                  | 13  | 14.1 | 5             | 26                                    | 1.0           | 110                                   | 0.1                                  | 10        |
| BZV55C15    | 13.8                  | 15  | 15.6 | 5             | 30                                    | 1.0           | 110                                   | 0.1                                  | 11        |
| BZV55C16    | 15.3                  | 16  | 17.1 | 5             | 40                                    | 1.0           | 170                                   | 0.1                                  | 12        |
| BZV55C18    | 16.8                  | 18  | 19.1 | 5             | 50                                    | 1.0           | 170                                   | 0.1                                  | 13        |
| BZV55C20    | 18.8                  | 20  | 21.1 | 5             | 55                                    | 1.0           | 220                                   | 0.1                                  | 15        |
| BZV55C22    | 20.8                  | 22  | 23.3 | 5             | 55                                    | 1.0           | 220                                   | 0.1                                  | 16        |
| BZV55C24    | 22.8                  | 24  | 25.6 | 5             | 80                                    | 1.0           | 220                                   | 0.1                                  | 18        |
| BZV55C27    | 25.1                  | 27  | 28.9 | 5             | 80                                    | 1.0           | 220                                   | 0.1                                  | 20        |
| BZV55C30    | 28                    | 30  | 32   | 5             | 80                                    | 1.0           | 220                                   | 0.1                                  | 22        |
| BZV55C33    | 31                    | 33  | 35   | 5             | 80                                    | 1.0           | 220                                   | 0.1                                  | 24        |
| BZV55C36    | 34                    | 36  | 38   | 5             | 80                                    | 1.0           | 220                                   | 0.1                                  | 27        |
| BZV55C39    | 37                    | 39  | 41   | 2.5           | 90                                    | 0.5           | 500                                   | 0.1                                  | 28        |
| BZV55C43    | 40                    | 43  | 46   | 2.5           | 90                                    | 0.5           | 600                                   | 0.1                                  | 32        |
| BZV55C47    | 44                    | 47  | 50   | 2.5           | 110                                   | 0.5           | 700                                   | 0.1                                  | 35        |
| BZV55C51    | 48                    | 51  | 54   | 2.5           | 125                                   | 0.5           | 700                                   | 0.1                                  | 38        |
| BZV55C56    | 52                    | 56  | 60   | 2.5           | 135                                   | 0.5           | 1,000                                 | 0.1                                  | 42        |
| BZV55C62    | 58                    | 62  | 66   | 2.5           | 150                                   | 0.5           | 1,000                                 | 0.1                                  | 47        |
| BZV55C68    | 64                    | 68  | 72   | 2.5           | 160                                   | 0.5           | 1,000                                 | 0.1                                  | 51        |
| BZV55C75    | 70                    | 75  | 80   | 2.5           | 170                                   | 0.5           | 1,000                                 | 0.1                                  | 56        |

Notes : 1. The zener Voltage ( $V_Z$ ) is tested under pulse condition of 10ms.

2. The device numbers listed have a standard tolerance on the nominal zener voltage of  $\pm 5\%$ .

3. For detailed information on price, availability and delivery of nominal zener voltages between the voltages shown and tighter voltage tolerances, contact your nearest Taiwan Semiconductor representative.

4. The zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an rms value equal to 10% of the dc zener current ( $I_{ZT}$  or  $I_{ZK}$ ) is superimposed to  $I_{ZT}$  or  $I_{ZK}$ .

Small Signal Product

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

Fig. 1 Power Dissipation VS. Ambient Temperature




Fig. 2 Total Capacitance




Fig. 3 Differential Impedance VS. Zener Voltage




Fig. 4 Forward Current VS. Forward Voltage




Fig. 5 Reverse Current VS. Reverse Voltage





Fig. 6 Reverse Current VS. Reverse Voltage



Small Signal Product


| ORDERING INFORMATION |                  |              |                     |         |                |
|----------------------|------------------|--------------|---------------------|---------|----------------|
| PART NO.             | MANUFACTURE CODE | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING        |
| BZV55Cxxx<br>(Note1) | (Note 2)         | L0           | G                   | LL34    | 10K / 13" Reel |
|                      |                  | L1           |                     |         | 2.5K / 7" Reel |

Note 1: "xxx" defines voltage from 2.4V (BZV55C2V4) to 75V (BZV55C75)

Note 2: Manufacture special control, if empty means no special control requirement.


| EXAMPLE         |          |                  |              |                     |                |
|-----------------|----------|------------------|--------------|---------------------|----------------|
| PREFERRED P/N   | PART NO. | MANUFACTURE CODE | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION    |
| BZV55C75 L0G    | BZV55C75 |                  | L0           | G                   | Green compound |
| BZV55C75-L0 L0G | BZV55C75 | L0               | L0           | G                   | Green compound |
| BZV55C75-B0 L0G | BZV55C75 | B0               | L0           | G                   | Green compound |

PACKAGE OUTLINE DIMENSION



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 3.30      | 3.70 | 0.130       | 0.146 |
| B    | 1.40      | 1.60 | 0.055       | 0.063 |
| C    | 0.20      | 0.50 | 0.008       | 0.020 |

SUGGEST PAD LAYOUT



| DIM. | Unit (mm) | Unit (inch) |
|------|-----------|-------------|
|      | Typ.      | Typ.        |
| A    | 1.25      | 0.049       |
| B    | 2.00      | 0.079       |
| C    | 2.50      | 0.098       |
| D    | 5.00      | 0.197       |

Small Signal Product

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Taiwan Semiconductor:

[BZV55C62](#) [BZV55C68](#) [BZV55C75](#) [BZV55C10](#) [BZV55C11](#) [BZV55C12](#) [BZV55C13](#) [BZV55C15](#) [BZV55C16](#)  
[BZV55C18](#) [BZV55C20](#) [BZV55C22](#) [BZV55C24](#) [BZV55C27](#) [BZV55C2V0](#) [BZV55C2V2](#) [BZV55C2V4](#) [BZV55C2V7](#)  
[BZV55C30](#) [BZV55C33](#) [BZV55C36](#) [BZV55C39](#) [BZV55C3V0](#) [BZV55C3V3](#) [BZV55C3V6](#) [BZV55C3V9](#) [BZV55C43](#)  
[BZV55C47](#) [BZV55C4V3](#) [BZV55C4V7](#) [BZV55C51](#) [BZV55C56](#) [BZV55C5V1](#) [BZV55C5V6](#) [BZV55C6V2](#) [BZV55C6V8](#)  
[BZV55C7V5](#) [BZV55C8V2](#) [BZV55C9V1](#)